

## Product Information

DE-F205



<b>Material description:</b>	White, woodfree, machine-coated, midgloss paper; material provides high degree of print contrast and high level of opacity; for application on dry, as well as humid, non-fatty food;
<b>Application:</b>	Universal label paper for quality multicolour labels requiring high contrast and fine printing detail
<b>Label stock thickness:</b>	70 µm, 80 g/m <sup>2</sup>
<b>Adhesive:</b>	AW2: acrylic adhesive, water based
<b>Adhesion:</b>	standard adhesive  Initial tack: 14,0 N FTM 9
<b>Liner:</b>	glassine paper, surface-sized
<b>Liner thickness:</b>	53 µm, 60 g/m <sup>2</sup>
<b>Temperature range:</b>	- 20 °C to + 80 °C
<b>Application temperature:</b>	> 0 °C
<b>Print method:</b>	thermal transfer, screen, flexography, offset
<b>Ribbon recommendation:</b>	DE-R21, DE-R58
<b>Shelf life:</b>	4 years at max. + 20 °C and 50 % r.h.

### Warranty:

Our recommendations are based on our most up-to-date knowledge and experience. As the products are used outside of our control we cannot take responsibility for any damage which may be caused when using the products. This product information sheet replaces all earlier ones. All information subject to change without notice.