

Product Information

DE-F919



Material description:	paper, white, wood-free, one-side coated, semi-glossy appearance; provides high colour contrasts and features high level of opacity; approved for direct contact with dry, moist, non-fatty foodstuffs
Application:	multi-purpose label, particularly useful for high-end, multi-colour labels requiring not only high level of contrast but also high level of register accuracy
Material thickness:	70 µm, 80 g/m ²
Adhesive:	CS2: rubber based, hot-melt adhesive
Adhesive thickness:	standard adhesion, good initial tack
Adhesion:	initial tack: 12,0 N FTM 9
Web material:	glassine paper, surface-sized
Web material thickness:	53 µm, 60 g/m ²
Temperature range:	- 40 ° C - + 60 ° C
Adhesion temperature:	> ± 0 ° C
Print methods:	thermal transfer print, silk screen printing, flexographic printing, offset printing
Ribbon recommendation	DE-R21, DE-R58
Storage/Shelf life:	2 years at max. + 20 ° C and 50 % r. h.

Warranty:

Our recommendations are based on our most up-to-date knowledge and experience. As the products are used outside of our control we cannot take responsibility for any damage which may be caused when using the products. This product information sheet replaces all earlier ones. All information subject to change without notice.

Dynamic Systems GmbH • Inninger Straße 11 • 82237 Wörthsee • Phone +49 8153 9096-0 • Telefax: +49 8153 9096-96
e-Mail: info@dynamic-systems.de • Internet: www.dynamic-systems.de • HRB Nr. 116251 Reg. Court Munich • V1.5

Creation Date: 2020-03-25