

## Product Information

DE-F 401



<b>Material description:</b>	Polyester film, white, matte, smear and scratch resistant, high level of resistance to chemicals, UL listing MH48716 <sup>*)</sup>		
<b>Applications:</b>	automotive and electronics industry		
<b>Label stock thickness:</b>	50 µm ± 10%		
<b>Adhesive:</b>	AS3: Acrylic adhesive, solvent-based		
<b>Adhesive thickness:</b>	21 - 25 µm		
<b>Adhesion:</b>	strong adhesive		
<b>Adhesion power:</b>	Stainless steel:	18,5 N/25 mm	FTM1
	Glass:	19,1 N/25 mm	FTM1
	Polypropylene:	16,9 N/25 mm	FTM1
	Car paint:	18,3 N/25 mm	FTM1
	PBT:	16,0 N/25 mm	FTM1
<b>Liner:</b>	glassine		
<b>Liner thickness:</b>	56 µm ± 10%		
<b>Temperature range:</b>	- 40 °C to + 150 °C		
<b>Application temperature:</b>	> + 10 °C		
<b>Print method:</b>	thermal transfer		
<b>Ribbon recommendation:</b>	DE-R89, DE-R25 <sup>*)</sup> , DE-R22 <sup>*)</sup> , DE-R21 <sup>*)</sup> (unprinted material surface)		
<b>Shelf life:</b>	2 years at max. 22 ° C and 50 % relative humidity		

<sup>\*)</sup> UL certified component 

### Warranty:

Our recommendations are based on our most up-to-date knowledge and experience. As the products are used outside of our control we cannot take responsibility for any damage which may be caused when using the products. This product information sheet replaces all earlier ones. All information subject to change without notice.

**Dynamic Systems GmbH** • Inninger Straße 11 • 82237 Wörthsee • Telefon: 08153/9096-0 • Telefax: 08153/9096-96  
e-Mail: info@dynamic-systems.de • Internet: www.dynamic-systems.de • HRB Nr. 116251 Reg. Gericht München • V1.3

create date 2016-08-02