

Product Information

DE-F417



| | |
|---------------------------------|--|
| Material description: | tamper-proof Polyester (chequerboard pattern remains on surface when label is being removed), top-coated for thermal transfer print, silver, matte |
| Label stock thickness: | 53 µm, 72 g/m ² |
| Adhesive: | solvent based permanent acrylic adhesive |
| Adhesive thickness: | 27 µm, 20 g/m ² |
| Adhesion: | high degree of initial tack and shear strength |
| Liner: | glassine |
| Liner thickness: | 58 µm, 65 g/m ² |
| Temperature range: | - 40 °C to + 120 °C |
| Application temperature: | > + 7 °C |
| Print method: | thermal transfer |
| Ribbon recommendation: | DE-R25 |
| Shelf life: | 2 years at 22 °C and 50 % relative humidity |

Warranty:

Our recommendations are based on our most up-to-date knowledge and experience. As the products are used outside of our control we cannot take responsibility for any damage which may be caused when using the products. This product information sheet replaces all earlier ones. All information subject to change without notice.

Dynamic Systems GmbH • Inninger Straße 11 • 82237 Wörthsee • Telefon: 08153/9096-0 • Telefax: 08153/9096-96
e-Mail: info@dynamic-systems.de • Internet: www.dynamic-systems.de • HRB Nr. 116251 Reg. Gericht München • V1.0

create date 2012-02-13