



<b>Material description:</b>	PP foil, white, glossy, thermo transfer printable, surface coated, high strength, heat-stabilized, temperature-consistent.
<b>Application:</b>	excellent consistency against water, oil and chemicals
<b>Label stock thickness:</b>	59µm, 58g/sqm
<b>Adhesive:</b>	AW1: acrylate adhesive, water-based
<b>Adhesion:</b>	slightly permanent adherent
<b>Adhesion power:</b>	adhesion power: stainless steel: 10 N/25 mm FTM 1 initial adhesion: glass: 9 N FTM 9 stainless steel: 9 N FTM 9 aluminium: 9 N FTM 9 shear strength: 10 h FTM 8
<b>Liner:</b>	glassine paper white, high transparent
<b>Liner thickness:</b>	60µm, 71g/sqm
<b>Temperature range:</b>	-40 °C to +130 °C above 90 °C, the resistance to long-term loads (> 1h) depends on the application and must be tested in a particular case
<b>Application temperature:</b>	> +5°C
<b>Printing type:</b>	thermal transfer printable
<b>Ribbon recommendation:</b>	DE-R93, DE-R99 DE-R55, DE-R51 (higher petrol resistance)
<b>Storage:</b>	2 year at 20-25 °C and 40-50% relative humidity

**Warranty:**

Our recommendations are based on our most up-to-date knowledge and experience. As the products are used outside of our control we cannot take responsibility for any damage which may be caused when using the products. This product information sheet replaces all earlier ones. All information subject to change without notice.